




1B7-GT



1B7-GT

PENTAGRID CONVERTER

Filament	Coated	
Voltage	1.4	d-c volts
Current	0.10	amp.
Direct Interelectrode Capacitances: ^o		
Grid #4 to Plate	0.34	μuf
Grid #4 to Grid #2	0.26	μuf
Grid #4 to Grid #1	0.12	μuf
Grid #1 to Grid #2	0.90	μuf
Grid #4 to All Other Electrodes (R-F Input)	7.0	μuf
Grid #2 to All Other Electrodes Except		
Grid #1 (Osc. Output)	4.2	μuf
Grid #1 to All Other Electrodes Except		
Grid #2 (Osc. Input)	4.0	μuf
Plate to All Other Electrodes (Mixer Output)	7.5	μuf
Maximum Overall Length	3-5/16"	
Maximum Seated Height	2-3/4"	
Maximum Diameter	1-5/16"	
Bulb	T-9	
Cap	Skirted Miniature, Style C	
Base	Sm. Wafer Octal 8-Pin, Sleeve	
Pin 1 - Base Sleeve	Pin 6 - Grid #2	
Pin 2 - Filament +	Pin 7 - Filament -	
Pin 3 - Plate	Pin 8 - No Connection	
Pin 4 - Grids #3 & #5	Cap - Grid #4	
Pin 5 - Grid #1		
Mounting Position	Any	



BOTTOM VIEW (GT-7Z)

CONVERTER SERVICE

Plate Voltage	110 max. volts	→
Screen (Grids #3 & #5) Voltage #	65 max. volts	→
Screen Supply Voltage	110 max. volts	→
Anode-Grid (Grid #2) Voltage	110 max. volts	→
Total Zero-Signal Cathode Current	4 max. ma.	→
Typical Operation and Characteristics:		
Plate	90	volts
Screen	45#	volts
Anode-Grid	90	volts
Control-Grid (Grid #4)*	0	volts
Oscillator-Grid (Grid #1) Resistor	200000	ohms
Plate Resistance	0.35	megohm
Conversion Transcond.	350	μmhos
Control-Grid Bias for Conversion		
Transcond. of approx. 2 μmhos	-14.5	volts
Plate Cur.	1.5	ma.
Screen Cur.	1.3	ma.
Anode-Grid Cur.	1.6	ma.
Oscillator-Grid Cur.	0.035	ma.
Total Cathode Cur.	4.4	ma.

NOTE: The transconductance of the oscillator portion (not oscillating) is 875 μmhos under the following conditions: plate volts, 90; screen volts, 45; control-grid volts, 0; anode-grid volts, 90; oscillator-grid volts, 0.

^o With close-fitting shield connected to negative filament terminal.

Obtained preferably by using a properly by-passed #5000- to 75000-ohm voltage dropping resistor in series with the supply voltage.

* A resistance of at least 1.0 megohm should be in the grid return to negative filament pin.

Typical Pentagrid Converter Circuit is shown under Type 146.

→ Indicates a change.

Dec. 1, 1941

RCA RADOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

TENTATIVE DATA